

## Cold Shrink Insulation Breakout

## MFZT

**Application**

- Used for cable termination separation up to 15kV.

**Color Standard: Grey****Feature**

- Quick and easy installation without heat source or tools.
- Good insulation and sealing properties.
- High track resistance.
- Superior hydrophobicity property.
- Outstanding corrosion and UV resistance.

**Standard**

- T/CEC118-2016

**For 1kV**

Type	Cross-section (mm <sup>2</sup> )	D1(mm)		D2(mm)		W(mm)
		Expanded	Recovered	Expanded	Recovered	Recovered Wall Thickness
<b>2-core</b>						
MFZT2-01-35/13-15/5	10-16	35	13	15	5	1.8
MFZT2-01-45/17-18/6	25-50	45	17	18	6	1.8
<b>4-core</b>						
MFZT4-01-55/22-18/6	25-50	55	22	18	6	2.2
MFZT4-01-70/29-25/8.5	70-120	70	29	25	8.5	2.2
MFZT4-01-90/39-32/12	150-240	90	39	32	12	2.2

**For 15kV**

Type	Cross-section (mm <sup>2</sup> )	D1(mm)		D2(mm)		W(mm)
		Expanded	Recovered	Expanded	Recovered	Recovered Wall Thickness
<b>3-core</b>						
MFZT3-15-85/37-30/11	25-50	85	37	30	11	3.0
MFZT3-15-100/44-40/14	70-120	100	44	40	14	3.0
MFZT3-15-110/54-45/18	150-240	110	54	45	18	3.5
MFZT3-15-125/60-55/22	300-400	125	60	55	22	3.0