

Cold Shrink Insulation Tubing

MJYG

Application

- Used for cable termination and intermediate connecting insulation protection up to 15kV.

Feature

- Quick and easy installation without heat source or tools.
- Good insulation and sealing properties.
- Superior hydrophobicity property.
- Outstanding corrosion and UV resistance.

Color Standard: Grey

Standard

- T/CEC118-2016



For 1kV termination insulation

Type	Cross-section (mm ²)	Expanded(mm)	Recovered(mm)	
		D(min)	d(max)	W(min)
MJYG-01-16/5	16	16	5	1.8
MJYG-01-19/6	25-50	19	6	1.8
MJYG-01-26/8	70-120	25	8	1.8
MJYG-01-35/12	150-240	35	12	1.8
MJYG-15-40/16	300-400	40	16	2.3

For 1kV joint insulation

Type	Cross-section (mm ²)	Expanded(mm)	Recovered(mm)	
		D(min)	d(max)	W(min)
MJYG-01-25/6	25-50	25	6	1.8
MJYG-01-30/8	70-120	30	8	1.8
MJYG-01-40/12	150-240	40	12	1.8
MJYG-15-50/16	300-400	50	16	2.3

For 15kV termination insulation

Type	Cross-section (mm ²)	Expanded(mm)	Recovered(mm)	
		D(min)	d(max)	W(min)
MJYG-15-35/12	25-50	35	12	2.3
MJYG-15-40/14	70-120	40	14	2.3
MJYG-15-45/16	150-240	45	16	2.3
MJYG-15-50/20	300-400	50	20	2.3

For 15kV termination sealing

Type	Cross-section (mm ²)	Expanded(mm)	Recovered(mm)	
		D(min)	d(max)	W(min)
MJYG-15-40/14	25-50	40	14	2.3
MJYG-15-45/16	70-120	45	16	2.3
MJYG-15-50/20	150-240	50	20	2.3
MJYG-15-58/23	300-400	58	23	2.3